



- NOTES:
- 1. APPROXIMATE HEIGHT = 8 5/16".
 - 2. FLANGE AAR APPROVAL # E-138514.
 - 3. CAP AAR APPROVAL # E-139515.
 - 4. THIS ASSEMBLY IS NOT DOT APPROVED AND CAN BE USED ONLY ON AAR STENCILED CARS.
 - 5. QUICK DISCONNECT MEETS A-A-59326D.
 - 6. GASKETS ARE WHITE FDA NITRILE.
 - 7. FITS JAMESBURY 6" WAFER SPHERE VALVE (9.00" B.C.).

NO.	PART NAME	PART #	REQ'D	MATERIAL
1	QUICK CONNECT CAP 4" KAMMED	K4NYDC02A	1	NYLON
2	QUICK CONNECT ADAPTER 4" FLANGED	K4SWF2	1	316 SS

UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES FRACTIONAL: ±1/16 X.XX: ±.03 X.XXX: ±.015 ANGULAR: ±1° DEBURR ALL SHARP EDGES. ALL MACHINED SURFACES TO HAVE A 125 RMS FINISH UNLESS NOTED OTHERWISE. THIRD ANGLE PROJECTION	DRAWN BY:	CHL	<div><div></div><div>SALCO PRODUCTS, INC.</div></div>		
	CHECKED BY:	ACC			
	PROTOTYPE BY:	CHL	QUICK CONNECT 4" FLANGED		
	PROTOTYPE DATE:	9/11/2002	MATERIAL: SEE BOM		
	APPROVED FOR PRODUCTION BY:	ACC	PROJECT #: 991213	SHEET #: 1 OF 1	SCALE: 1:1
	PRODUCTION DATE:	9/15/2011	DRAWING #: D17281	PART #: K4NYSWF2A	