


SALES DRAWING

SALES DRAWING

- NOTES:
1. APPROXIMATE HEIGHT = 7 7/8".
  2. AAR APPROVAL# E-139514.
  3. THIS ASSEMBLY IS NOT DOT APPROVED AND CAN BE USED ONLY ON AAR STENCILED CARS.
  4. QUICK DISCONNECT MEETS A-A-59326D.
  5. GASKETS ARE BLACK NITRILE.
  6. FITS JAMESBURY 6" WAFER SPHERE VALVE (9.00" B.C.).

UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES FRACTIONAL: ±1/16 X.XX: ±.03 X.XXX: ±.015 ANGULAR: ±1° DEBURR ALL SHARP EDGES. ALL MACHINED SURFACES TO HAVE A 125 RMS FINISH UNLESS NOTED OTHERWISE. THIRD ANGLE PROJECTION	DRAWN BY:	BRG
	CHECKED BY:	CHL
	PROTOTYPE BY:	BRG
	PROTOTYPE DATE:	6/17/2008
	APPROVED FOR PRODUCTION BY:	CHL
	PRODUCTION DATE:	6/17/2008

A	RJP	12-20-13	AAR APPROVAL # WAS E-039015, MIL SPEC WAS MIL-C-27487G		
REV	BY	DATE	DESCRIPTION		
			 <b>SALCO PRODUCTS, INC.</b>		
			PART NAME: <b>QUICK CONNECT 4" FLANGED</b>		
			MATERIAL: <b>316 SS</b>		
PROJECT #:		WAG0575		SHEET #:	1 OF 1
DRAWING #:		D25462		PART #:	K4SWF1A
				SCALE:	1:1