7. CASTINGS ARE DUCTILE IRON (FERRITIZED/ANNEALED) AND MEET ASTM A395 GRADE 60-40-18 REQUIREMENTS.

VIEW A

SCALE 3:4

- 6. QUICK DISCONNECT MEETS A-A-59326D SPECS.
- 5. THIS ASSEMBLY IS AAR AND DOT APPROVED.
- 4. AAR APPROVAL # E-149523.

- 3. FITS 4" JAMESBURY BALL VALVE (AZFRC) 9.00" B.C.

1. APPROXIMATE HEIGHT: 8"

2. GASKET THICKNESS: 1/4"

 $\rightarrow$ 

NOTES:

0 GYLON® 3545 GASKET

5	$\downarrow$		4 3
		NO.	PART NAME
		1	QUICK CONNECT CAP 4" THREADED
		2	QUICK CONNECT ADAPTER 4" FLANG

2		

					В	נן
					A	K
					IREV	E
	UNLESS OTHERWISE S DIMENSIONAL TOLEF		DRAWN BY:	КНК		
	FRACTIONAL:	$\pm 1/16$				
	X.XX:	±.03	CHECKED BY:	CHL		1E:
	x.xxx:	±.015	PROTOTYPE BY:	КНК	Q	Ľ
	ANGULAR:	±1°				
	DEBURR ALL SHARP ALL MACHINED SURF/	ACES TO	PROTOTYPE DATE:	9/12/2013	MATERIAL	
	HAVE A 125 RMS FINISH UNLESS NOTED OTHERWISE.		APPROVED FOR PRODUCTION BY:	WRB	PROJECT	
	THIRD ANGLE PROJE	CTION			DRAWING	#:
INFORMATION			PRODUCTION DATE:	10/25/2013	D	
	4	I		3		

THIS PRINT, PROPERTY OF SALCO PRODUCTS INC, CONTAINS PROPRIETARY AND MUST NOT BE COPIED, REPRODUCED, OR USED DETRIMENTALLY TO OU

