





The new GATOR® hopper car outlet gate significantly improves the unloading of grain, fertilizer, corn, and other dry and light commodities.



FEATURES & BENEFITS

- Available in 30"x 30" or 42"x 42" sizes
- · Leak Proof Reinforced Bolting Flange
- Low Operating Torque
- No Pinion Skipping
- Rolled Flange Construction
- Smooth Hopper Surface Allows for Uninterrupted Flow
- · Low Wear, High Strength Capstan
- Durable Automatic Lock
- Self-Cleaning
- · Light Weight Construction
- Security Seal Tab

DEPENDABLE & EFFECTIVE

The Stucki GATOR® outlet gate features polyethylene door seals for ease of operation, an automatic locking door plate mechanism, and a self-cleaning door wiper.

THE FIRST OF ITS KIND

A new security mechanism has been engineered to deter door-plate theft. This vital feature is the first of its kind in the rail industry.



www.stucki.com



Ofc: 412-424-0560 sales@stucki.com





• 360 Wright Brothers Dr. Moon Township, PA 15108



Hopper Car



ADDITIONAL CUSTOMIZED OPTIONS

- Stainless Steel Hardware
- Available in 7 ga Steel
- Variety of Powder-Coated Options

Part Number: SBH-AC04A01*

- **Food Grade Quality**
- **Heavy Duty Bolt-on Frame**
- Standard 66 Bolt Pattern
- **Weld-on Version**

42"x 42" GATOR® OUTLET GATE

ADDITIONAL BENEFITS

AAR S-233 approved.

- Lighter than current models without sacrificing strength.
- High quality, flexible UHMW seals are easy to replace.
- Low torque operation for easy unloading and closing.
- Efficient design helps door to catch on gears when inserting after reassembly.
- Strong and secure locking mechanism indicates lock status and is easily visible trackside.
- Doors can be removed without removing operating shaft.
- Cam system ensures that the locks do not drag on the gate door while opening and closing.
- *Part numbers listed are for images shown. Please contact Customer Service for additional options.

Industry Size Reference 30" x 30" 42" x 42"
Bolt-On Working Points 45-3/8" x 43-3/8" 45-3/8" x 43-3/8"
Weld-On Working Points 45-3/8" x 43-3/8" 45-3/8" x 43-3/8"
Actual Gate Opening Size 31-3/4" x 29-3/4" 41-7/8" x 39-7/8"
Bottom Frame Opening 34-1/2" x 32-7/8" 48-3/4" x 43-7/16"
Flange to Flange Height 9-3/4" 7-3/8"
Overall Gate Height 10-3/4" 7-15/16"
Number of Bolt Holes 66 66
Weight 344 lbs. 575 lbs.
Centerline of Opening to Edge of Fully Open Door 53-13/16" 69-11/16"

www.stucki.com



Ofc: 412-424-0560 🖂 sales@stucki.com





360 Wright Brothers Dr. Moon Township, PA 15108