


NO.	PART NAME	PART #	REQ'D	MATERIAL
1	QUICK CONNECT CAP 4" KAMMED	K4ICDC6A	1	DUCTILE IRON
2	QUICK CONNECT ADAPTER 4" FLANGED	K4ITF	1	DUCTILE IRON

- NOTES:
- 1. APPROXIMATE HEIGHT 6-7/8"
 - 2. AAR APPROVAL # E-139514.
 - 3. THIS ASSEMBLY IS NOT DOT APPROVED AND CAN BE USED ONLY ON AAR STENCILED CARS.
 - 4. QUICK DICONNECT MEETS A-A-59326D.
 - 5. CASTINGS ARE DUCTILE IRON (FERRITIZED/ANNEALED) AND MEET ASTM A395 GRADE 60-40-18 REQUIREMENTS.
 - 6. CAP GASKET IS BLACK VITON A.
 - 7. SPRAY WITH USDA APPROVED WHITE MINERAL OIL OR VEGETABLE OIL AS A RUST INHIBITOR.
 - 8. FITS TRINITY/UNION TANK 4" BALL VALVE (7.75" BC)

UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES		DRAWN BY:	CHL	B RJP 10-31-13 AAR APPROVAL # WAS E-019022, MIL SPEC WAS MIL-C-27487G	
		CHECKED BY:	ACC	A CHL 4-13-07	NEW PART ADDED TO SYSTEM
		PROTOTYPE BY:	CHL	REV BY	DATE DESCRIPTION
FRACTIONAL: ±1/16		PROTOTYPE DATE:	3/26/2007	<div> SALCO PRODUCTS, INC.</div> <div>QUICK CONNECT 4" FLANGED</div>	
X.XX: ±.03		APPROVED FOR PRODUCTION BY:	ACC		
X.XXX: ±.015		PRODUCTION DATE:	4/13/2007	MATERIAL: SEE BOM	
ANGULAR: ±1°				PROJECT #: WAG0411	SHEET #: 1 OF 1
THIS PRINT, PROPERTY OF SALCO PRODUCTS INC., CONTAINS PROPRIETARY INFORMATION AND MUST NOT BE COPIED, REPRODUCED, OR USED DETRIMENTALLY TO OUR INTEREST.		THIRD ANGLE PROJECTION		DRAWING #: D23357	PART #: K4ITCUF06A
				SCALE: 1:1	